

Please amend Claim 21 as follows:

21. The apparatus of claim 16, wherein the server is adapted for assigning an identifier to the legacy output data for identifying the legacy device.

Please amend Claim 22 as follows:

22. The apparatus of claim 16, wherein the transmitter is the Ethernet.

Please amend Claim 23 as follows:

23. The apparatus of claim 16, wherein the networked system includes networked appliances responsive to an event, and wherein an output signal from a legacy device will activate an appliance response.

Please amend Claim 24 as follows:

24. The apparatus of claim 16, wherein the networked system includes a camera activated by an event in the camera zone, and wherein an output signal from a legacy device in the zone of the camera will activate the camera.

Please amend Claim 25 as follows:

25. The apparatus of claim 16, including a plurality of legacy devices, each producing an unique legacy output signal, each of which is transmitted to the networked system by the transmitter.

Please amend Claim 28 as follows:

28. The apparatus of claim 16, including plurality of legacy systems, each system including a legacy device producing a legacy output signal, and wherein the plurality of legacy systems are not compatible with one another.

Please add new claims 29-33, which contain no new matter, as follows:

29. A method for capturing legacy data using a legacy serial output port, comprising:
testing an input port;

if legacy data is being received from the input port, testing a legacy serial output port; testing a socket connection to a server; determining if a log is open; if the log is open, writing the data to the log; writing the data to the output port; and writing the data to the socket.

30. A method for capturing legacy data using a legacy system computer, comprising:
 - reading a legacy database;
 - saving the read database in a legacy server;
 - if the database changes, logging the change;
 - checking a socket connection to the server; and
 - if the socket is connected to the server, writing the changes to the socket.
31. A method for capturing legacy data using a legacy serial output port, comprising:
 - testing an input port;
 - if legacy data is being received from the input port, testing a legacy serial output port;
 - testing a socket connection to a server;
 - writing the data to the output port; and
 - writing the data to the socket.
32. A method for capturing legacy data, comprising:
 - capturing legacy device data in a multi-media system server;
 - creating a socket;
 - reading the legacy data from the socket; and
 - storing the legacy data in a database associated with the server.
33. A method for managing legacy data, comprising:
 - receiving a legacy alert signal at a multi-media system server; and
 - zooming, by a camera, to a location of the alert based on the proximity of the camera to the location.